

Redefining the Large-Format Printer. imagePROGRAF TM Series

Up to 3.2 D Prints/Minute Vivid, Eye-Catching Prints, with New Magenta Ink

Scan-to-Copy/File/ Share Solution



imagePROGRAF TM-350 MFP Lm36

Specifications

Print Head PF-06

Number of Nozzles

Matte Black: 5,120 Nozzles

Other Colors: 2,560 Nozzles per Color Droplet Size

5 Picoliter

Ink Type

Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)

Ink Tank

Shipped with printer: MBK (130 ml), BK, C, M, Y (90 ml) Replacement: MBK, BK, C, Y: PFI-320 (300 ml)/PFI-120 (130ml) and M: PFI-321 (300 ml)/PFI-121 (130 ml)

Printer RAM

2 GB

Media Feed

Roll Feed: One Roll, Top-loading, Front Output

Media Width

Roll Feed: 8"-36" (203.2 - 917mm) Cut Sheet: 8"-36" (203.2 - 917mm)

Media Cutter

Automatic horizontal cutting (Rotary cutter): standard

Media Thickness 0" - 0.03" (0.07 mm - 0.8 mm)

Media Core Sizes

2" Core Standard. 2"/3" Core Roll Holder Set (RH2-35) Included

Maximum Roll Outer Diameter

5.9" (150 mm)

Media Output

Stackable Basket

Printing Software Utilities

Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows[®]/Mac[®], Media Configuration Tool, PosterArtist Lite, Canon PRINT Inkjet Selphy

Operating System

Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), Macintosh OS v10.12.6-v13x

Print Language

Printer: SGRaster, HP-GL/2, HP RTL, JPEG, CALS G4

Interface

Standard (Built-in): USB 2.0 Hi-Speed, 10/100/ 1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)■

Power Supply

AC 100 - 240V (50 - 60 Hz)



©2023 Canon U.S.A., Inc. All rights reserved.

9/23-1912-9304

not warrant that use of its features will prevent security issues.

Power Consumption

Max: Approx. 65W Standby: Approx. 1.6W Power Off: Approx. 0.1W

Certifications Environmental Certifications ENERGY STAR® (Worldwide), EPEAT Gold

Operational Environment Temperature: 59 – 86 °F (15 – 30 °C) Relative Humidity: 10 – 80% (Non Condensation)

TM-350 MFP Lm36 Dimension (H x W x D) and Weight 50.24" x 50.6" x 34.2" Approx. 155.4 lb

Package Dimensions (H x W x D) and Weight 31.5" x 57.6" x 35.9" Approx. 224.9 lb

Options

- 2//3" Roll Holder Set (RH2-35)
 User-Replaceable Items
 Ink Tank (300 ml: PFI-320/PFI-321, 130ml: PFI-120/PFI-121)
- Print Head (PF-06)
 Maintenance Cartridge (MC-31)
- Cutter Blade (CT-08)

What's In The Printer Box

Printer, Stand with Stackable Basket, Starter Ink Tanks BK/C/M/Y (90ml) MBK (130ml), 1 Print Head, Maintenance Cartridge (Installed), 2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, One Year Printer Warranty Statement, Print Head Warranty Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice Flyer, Safety and Environmental Information, iWR Service Terms Leaflet, USB port (High Speed), Power Cable and Screw, Gigabit Ethernet (Built-in)

Lm36 SCANNER

Scan Speed

Color: 1" per second at 200dpi
 Mono or B/W: 3" per second at 200dpi

Scan Modes

- 16.7 Million Color RGB (24-bit)
- 256-level Grayscale (8-bit)

• Black-and-white (1-bit)

Color Space

sRGB

36

Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does

Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Some security features may impact functionality/performance; you may want to test these settings in your environment.

As an ENERGY STAR[®] Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Wi-Fi is a registered trademark of the Wi-Fi alliance. All other referenced product names and marks are trademarks of their respective owners. All printer output and screen

images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors

Maximum Resolution 600 dpi (Optical)

Scan Accuracy

+/- 0.2% : +/- 1 pixel

Maximum Scan Width

imagePROGRAF

TM-350 MFP Lm36

Maximum Media Width

38"

Maximum Scan Length 109" (PDF)

Maximum Media Thickness 0.003" - 0.03" (0.07 mm - 0.8 mm)

Digital Imaging Technology

Contact Image Sensor (CIS) Technology (SingleSensor Assembly)

- 24-bit RGB digital color image capture
- 16-bit grayscale image capture
- Panchromatic monochrome and black-and-white
 Bi-directional extra long-life LED light system for
- optimum object illumination and instant-on scanning capability

Included Software

ScanAppL

Operating Environment

10 - 35 °C, 10 - 90% RH

External Power Supply

100 - 240 VAC +/- 10%, 50 - 60 Hz

Scanner Power Consumption Sleep/Idle: 0.6W/11.7W

Scanning Color/Grayscale @ 200 dpi: 17.5W

Compliance

ENERGY STAR®, UL, FCC

Scanner Dimensions (H x W x D)

(With Doc Return Guide - Paper Tray flat) 5.2" x 48.7" x 10"

Scanner Weight

14.5 lbs

What's In The Scanner Box?

- Lm36 Scanner
 Printer mounting brackets, fixings, and 3mm tool
- 2 paper edge guides
- Document return guides (3 for Lm36)
- Calibration target
- Lm36 Scanner Quick Start Guide
- Ethernet cable (2 meter)
- Power supply

Power Supply Regional - Mains power cord(s) (2 meter)

- Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.
- The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance. Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types.
- The quoted scan accuracy may vary depending on the operating environment and the thickness of the media.

Note: The imagePROGRAF TM Series MFP Lm36 systems contain multiple components, some of which are manufactured by third parties. To the extent that such third-party offerings come with limited warranties, such limited warranties are hereby passed to the purchaser, and Canon shall have no obligation or any liability with respect to such third-party offerings.

usa.canon.com/imagePROGRAF

F 📡 (ð) D 🛅

e Rea